Specification

	Model	DW-86L579BPT	DW-86L729BPT	DW-86L829BPT	DW-86L959BPT
Technical Data	Cabinet Type	Upright	Upright	Upright	Upright
	Climate Class	N	N	N	N
	Cooling Type	Direct cooling	Direct cooling	Direct cooling	Direct cooling
	Defrost Mode	Manual	Manual	Manual	Manual
	Refrigerant	HC	HC	HC	HC
	Noise((dB(A))	43.5	43.5	43.5	47
Performance	Cooling Performance(℃)	-86	-86	-86	-86
	Temp Range(℃)	-40～-86	-40～-86	-40～-86	-40～-86
Control	Controller	Microprocessor	Microprocessor	Microprocessor	Microprocessor
	Display	LCD	LCD	LCD	LCD
Electrical Data	Power Supply(V/HZ)	100～230/50/60	100～230/50/60	208～230/50/60	208～230/50/60
	Power(W)	1100	1100	1100	1300
	Electrical Current(A)	6	6	6	7
Dimensions	Capacity(L/Cu.Ft)	579/20.4	729/25.7	829/29.2	959/33.9
	Net/Gross Weight	325/355	350/385	380/415	450/485
	(approx)	716.5/782.6	771.6/848.8	837.7/914.8	992.1/1069.2
	Interior Dimension	620*716*1310	766*716*1310	870*716*1310	1016*716*1310
	(W*D*H)	24.4*28.2*51.6	30.2*28.2*51.6	34.3*28.2*51.6	40.0*28.2*51.6
	Exterior Dimension	895*998*1980	1046*998*1980	1145*998*1980	1296*998*1980
	(W*D*H)	35.4*39.3*78.0	41.2*39.3*78.0	45.1*39.3*78.0	51.0*39.3*78.0
	Packing Dimension	950*1055*2150	1100*1105*2150	1190*1045*2150	1365*1105*2150
	(W*D*H)	37.4*41.5*84.6	43.3*43.5*84.6	46.9*41.1*84.6	53.7*43.5*84.6
	Container Load(20'/40'/40'H)	12/24/24	10/20/20	8/20/20	8/16/16
Functions	Remote Alarm	Y	Y	Y	Y
	High/Low Temp	Y	Y	Y	Y
	Hot Condenser	Y	Y	Y	Y
	Power Failure	Y	Y	Y	Y
	Sensor Error	Y	Y	Y	Y
	Low Battery	Y	Y	Y	Y
	High Ambient Temp	Y	Y	Y	Y
	Door Ajar	Y	Y	Y	Y
Accessories	Caster	Y	Y	Y	Y
	Foot	Y	Y	Y	Y
	Test Hole	Y/2	Y/2	Y/2	Y/2
	Shelves/ Inner Doors	3/4	3/4	3/4	3/4
	USB Interface	Y	Y	Y	Y
	5V Power Supply Port	Y	Y	Y	Y
	Temp Recorder	Optional	Optional	Optional	Optional
	485 Port	Standard	Standard	Standard	Standard
	CO2 Backup System	Optional	Optional	Optional	Optional
	LN2 Backup System	Optional	Optional	Optional	Optional
Others	Certificate	CE、UL	CE、UL	CE、UL	CE、UL

Tel:+86-0532-88935955
Website:www.haiermedical.com